





A 1 temperature cabinet adjustable from 9 to 15° to mature your wines in the best possible conditions.





EAN Code: 3543290002776

CONFIGURATION	Storage shelves	Sliding shelves	Capacity**
Maximum Configuration (100% sliding)	-	5	74
Mixed Configuration	I	1	98
Minimum Configuration (100% storage)	1	1	98
Standard Configuration	I	1	98

UNIVERSAL SHELF

Universal shelf: AOHUI

Weight: 2.6 kg

Type of structure: slats

Number of bottles per level: 12

Material: Solid Beechwood coated with an ecological water varnish.

AOHUI shelf is universal. It can be positioned in







« **Storage**» 72 Bottles

« Sliding»

« Presentation »

Artevino AOHUI shelf has a label holder:



Description	Reference	EAN Code
Single Solid beechwood universal shelf	AOHUI	3543290002783

- Standard configuration
- Traditional Bordeaux bottles
- Calculated with an ambient temperature of 32°C
- ***** Consumption calculated with an ambient temperature of 25°C using an appliance with standard configuration
- R600a gas. With a R134a gas (for US, CA, Korea, Taïwan): 38 db(A)

Range : OXYGEN

Model : OXP1T98NPD

Fonction: Ageing

Capacity*: 98 Bottles**

A constant temperature due to the dual Heating/Cooling controls.

6

Optimised humidity due to the circulation of humid air.



Air circulation ensured by the principle of thermodynamic pump.



No vibration thanks to the slow-cycles compressor fixed on silentblocs + evaporator flooded in the high density polyurethane foam.



Protection from UV light guaranteed with a solid door with highly effective UV filter.



« Storage and/or sliding » universal shelf. One shelf for all types of storages. Suitable to store all types of bottles.

GENERAL FEATURES

Gross weight, packaged(kg)* : 63,7Net weight (kg)* : 50,2

Dimensions in packaging $H \times W \times D$ (mm) : $1070 \times 700 \times 750$ Dimensions $H \times W \times D$ (mm) : $960 \times 680 \times 700$

Color scheme : Black

Energy efficiency rating : A+

Acoustic emissions (dB(A))***** : 37

Electrical power (W)*** : 60

Electrical intensity (A)*** : 0.28

Consumption per 24h (KWh) **** : 0.31

Annual energy consumption AEc* (kWh/year) **** : 114

Ambient temperature operating limit : 0 - 35°C

- √ Digital electronic controls
- √ Temperature display on indoor sidewall
- ✓ Double Hot/ Cold circuit > Automatic « Winter function »
- √ Temperature fault alarm icon
- √ Interior lining of dimpled aluminium
- ✓ Solid door
- √ Hygrometry ensured by the principle of thermodynamic pump
- ✓ 2 adjustable feet
- ✓ Lock
- √ Storage grid in the low part
- √ Inox Handle